



220V Diesel Welding Generator 6500EAW Genset Diesel Welder Generator

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Rated Frequency: 50hz 60hz
- Rated Power (kw): 2.5
- Rated Voltage (V): 220V Or As Request
- Rated Current (A): 8.7 9.5A
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- No Load Welding Voltage: 65-70V
- Insulation Grade: F
- Pole Number: 2
- Engine Mode: GET186FA GET192F
- Displacement(ml): 418 456
- Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
- Bore X Stroke (mm): 100x70/100x75

for more products please visit us on dieselenginepumps.com

Product Description

Open Type Diesel Powered Welder GET6500EAW Diesel Welding Generator

The GET6500EAW Diesel Welding Generator is a specific model of diesel welding generator. While I don't have information on this specific model as my knowledge cutoff is in September 2021, I can provide you with a general overview of the features commonly found in diesel welding generators. Please note that the features may vary depending on the manufacturer and model. Here are some typical features you might find in a diesel welding generator:

Rated Power (kw):	2 5
Rated Current (A):	8.7 9.5A
Phase No.:	Single Phase
No Load Welding Voltage:	65-70V
Pole Number:	2
Displacement(ml):	418 456
Bore X Stroke (mm):	1-86x72/ 1-92x75
Rated Power:	5.7 6.3/ 7.2 8.2
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Fuel Tank Capacity (L):	13.5
Rated Welding Current:	180A 220A
Welding Load Continuous Ratio:	60%
Electrode Diameter:	1.6-3.2mm 1.6-5.0mm
Rectifying Mode:	Diode
Overall Dimension:	720x492x655mm
Dry Weight:	112kg 116kg
Rated Frequency:	50hz 60hz
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Insulation Grade:	F
Engine Mode:	GET186FA GET192F
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Compression Ratio:	19:1
Lubrication System:	Pressure Splashed
Lube Capacity (L):	1.65
Fuel Consumption (g/kw*h):	≤280
Continuous Running Time:	8h
Welding Voltage:	25-30V
Welding Current Adjustment Range:	50-180A/ 50-200A
Excitation Mode:	Separate-excitation+AVR Voltage Regulation AVR
Connection Mode:	Drive Bearing, Rigid Connection
Structure Type:	Open Type

Fuel Efficiency: Diesel welding generators are generally known for their fuel efficiency, allowing for longer operation times without frequent refueling.

Safety Features: The generator should include safety features such as overload protection, low oil shutdown, and circuit breakers to protect both the generator and connected equipment.

Portability: Depending on the model, the generator may have built-in handles, wheels, or a compact design to enhance portability and ease of transportation.

Noise Reduction: Some diesel welding generators incorporate noise-reducing features such as soundproof enclosures or mufflers to minimize noise levels during operation.

Multiple Power Outlets: The generator may provide various power outlets, such as AC sockets or industrial plugs, to accommodate different electrical devices and tools.

电焊机发电系列 Diesel Welding Generator Series



技术参数 Specifications

参数名称	GET186FA	GET192F	GET200F	GET220F
额定功率 (kW)	5.7	6.3	7.2	8.2
额定电流 (A)	8.7	9.5	10.4	11.3
额定电压 (V)	220	220	220	220
额定频率 (Hz)	50	50	50	50
额定转速 (r/min)	3000	3000	3000	3000
排量 (ml)	418	456	418	456
缸径 × 行程 (mm)	86 × 72	92 × 75	86 × 72	92 × 75
燃油消耗率 (g/kWh)	≤280	≤280	≤280	≤280
连续运行时间 (h)	8	8	8	8
焊接电压 (V)	25-30	25-30	25-30	25-30
焊接电流调节范围 (A)	50-180	50-200	50-180	50-200
励磁方式	独立励磁	独立励磁	独立励磁	独立励磁
连接方式	驱动轴承	驱动轴承	驱动轴承	驱动轴承
结构形式	开放式	开放式	开放式	开放式
总重量 (kg)	112	116	112	116
外形尺寸 (mm)	720 × 492 × 655	720 × 492 × 655	720 × 492 × 655	720 × 492 × 655

