



## 3000rpm 3600rpm Portable Diesel Welding Generator Set Low Noise

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



### Product Specification

- Rated Frequency: 50hz 60hz
- Rated Power (kw): 2.5
- Rated Voltage (V): 220V Or As Request
- Rated Current (A): 8.7 9.5A
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- No Load Welding Voltage: 65-70V
- Insulation Grade: F
- Pole Number: 2
- Engine Mode: GET186FA GET192F
- Displacement(ml): 418 456
- Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
- Bore X Stroke (mm): 100x70/100x75

for more products please visit us on [diesenginepumps.com](http://diesenginepumps.com)

## Product Description

### Low Noise Diesel Powered Welder Generator GET6500EAW Diesel Powered Welding Machine

The GET6500EAW Diesel Welding Generator is a specific model of diesel welding generator. While I don't have information on this specific model as my knowledge cutoff is in September 2021, I can provide you with a general overview of the features commonly found in diesel welding generators. Please note that the features may vary depending on the manufacturer and model. Here are some typical features you might find in a diesel welding generator:

|                                   |                                                                      |
|-----------------------------------|----------------------------------------------------------------------|
| Rated Power (kw):                 | 2 5                                                                  |
| Rated Current (A):                | 8.7 9.5A                                                             |
| Phase No.:                        | Single Phase                                                         |
| No Load Welding Voltage:          | 65-70V                                                               |
| Pole Number:                      | 2                                                                    |
| Displacement(ml):                 | 418 456                                                              |
| Bore X Stroke (mm):               | 1-86x72/ 1-92x75                                                     |
| Rated Power:                      | 5.7 6.3/ 7.2 8.2                                                     |
| Lube Oil Brand:                   | CD Grade Or SAE10W-30, 15W-40                                        |
| Fuel Type:                        | 0#(summer)-10#(winter)-35#(chillness) Diesel                         |
| Fuel Tank Capacity (L):           | 13.5                                                                 |
| Rated Welding Current:            | 180A 220A                                                            |
| Welding Load Continuous Ratio:    | 60%                                                                  |
| Electrode Diameter:               | 1.6-3.2mm 1.6-5.0mm                                                  |
| Rectifying Mode:                  | Diode                                                                |
| Overall Dimension:                | 720x492x655mm                                                        |
| Dry Weight:                       | 112kg 116kg                                                          |
| Rated Frequency:                  | 50hz 60hz                                                            |
| Rated Voltage (V):                | 220V Or As Request                                                   |
| Rated Rotation Speed (r/min):     | 3000 3600                                                            |
| Power Factor:                     | 1                                                                    |
| Insulation Grade:                 | F                                                                    |
| Engine Mode:                      | GET186FA GET192F                                                     |
| Engine Type:                      | Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled |
| Compression Ratio:                | 19:01                                                                |
| Lubrication System:               | Pressure Splashed                                                    |
| Lube Capacity (L):                | 1.65                                                                 |
| Fuel Consumption (g/kw*h):        | ≤280                                                                 |
| Continuous Running Time:          | 8h                                                                   |
| Welding Voltage:                  | 25-30V                                                               |
| Welding Current Adjustment Range: | 50-180A/ 50-200A                                                     |
| Excitation Mode:                  | Seperate-excitation+AVR Voltage Regulation AVR                       |
| Connection Mode:                  | Drive Bearing, Rigid Connection                                      |
| Structure Type:                   | Open Type                                                            |

**Power Output:** Diesel welding generators are capable of providing electrical power output ranging from a few kilowatts to several tens of kilowatts. The specific power output of the GET6500EAW model would need to be checked with the manufacturer or the product specifications.

**Welding Capability:** The generator will have built-in welding capabilities, such as arc welding or stick welding. It may offer adjustable welding parameters such as amperage and voltage to suit different welding applications.

**Diesel Engine:** The generator is powered by a diesel engine known for its reliability and fuel efficiency. The engine should have sufficient power to drive both the generator and the welding system.

**Welding Controls:** The generator will have controls for adjusting welding parameters, such as amperage and voltage. These controls allow the operator to set the desired welding conditions for optimal performance.

**Electric Start:** The generator may feature an electric start system, which allows for easier and quicker startup compared to manual starting methods.

电焊发电系列 Diesel Welding Generator Series



参数表 Specifications

| 型号 Model             | 10-15000EAW | 10-15000EAW | 10-15000EAW |
|----------------------|-------------|-------------|-------------|
| 额定功率 Rated frequency | 50          | 60          | 50          |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              | 86          | 92          | 86          |
| 行程 Stroke            | 72          | 75          | 72          |
| 额定功率 Rated power     | 5.7         | 6.3         | 5.7         |
| 额定电压 Rated voltage   | 220V        | 220V        | 220V        |
| 额定电流 Rated current   | 8.7         | 9.5         | 8.7         |
| 额定转速 Rated speed     | 3000        | 3600        | 3000        |
| 排量 Displacement      | 418         | 456         | 418         |
| 缸径 Bore              |             |             |             |



**Wuxi Guangertai Power Machinery Co.,Ltd**



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City,CHINA