



192F 186FA Portable Diesel Fire Pump Portable Water Pump For Fire Fighting

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Portable Diesel Fire Pump
- Suction/discharger Port Diameter Mm(inch): 50(2'). 80(3'). 100(4'). 150(6')
- Discharge Capacity m³/h: 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m: 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 300 410 400

for more products please visit us on dieselenginepumps.com

Product Description

High Efficiency Diesel Pump For Fire Fighting Industrial Use

Fire pump is a kind of pump equipment specially used for fire extinguishing and fire emergency. It has the following characteristics:

1. Durability and Reliability: Fire pumps need to work reliably during emergencies, so they usually have a durable and reliable design. They are manufactured with high-quality materials and components to ensure reliable operation in harsh environments such as high pressure and temperature.
2. Portability: Since fire pumps usually need to be used for fire extinguishing operations in different places, portability is one of its important features. They are typically designed as portable or mobile devices that can be easily transported to a fire scene to provide rapid fire suppression support.
3. Automatic control system: In order to facilitate operation and monitoring, many fire pumps are equipped with automatic control systems. These systems can realize automatic start and stop, pressure control and monitoring to ensure that the fire pump remains stable and efficient during work.

| | |
|------------------------------------|--------------------|
| Model | JBC6/10 |
| Type | vacuum pump |
| Max.Flow(T/h) | 48 |
| MAX.Lift(m) | 60 |
| Rated Speed(rpm) | 3600 |
| Water Shot Height | 35m |
| Engine | 190F |
| Maximum Suction Height(m) | 7 |
| Self-priming Time(S) | 20 |
| Discharge Port Diameter(mm) | 65 |
| N.W/G.W(KG) | 91/100 |
| Dimensions(mm) | |
| Loading Qty(20GP/40HQ) | |
| Model | JBC6/15 |
| Type | vacuum pump |
| Max.Flow(T/h) | 54 |
| MAX.Lift(m) | 80 |
| Rated Speed(rpm) | 3600 |
| Water Shot Height | 35 |
| Engine | 192 |
| Maximum Suction Height(m) | 7 |
| Self-priming Time(S) | 20 |
| Discharge Port Diameter(mm) | 65 |
| N.W/G.W(KG) | 94/103 |
| Dimensions(mm) | |
| Loading Qty(20GP/40HQ) | |





Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA